

ASP-105 R

WIRELESSLY TRIGGERED OUTDOOR SIREN

- wireless triggering of optical and acoustical signaling
- optical signaling: ultra bright LEDs
- selection of four acoustic signals
- remote configuration
- long-lasting rechargeable battery powered by external power supply
- tamper protection:
 - against opening
 - against removing from mounting surface
- available also in blue (**ASP-105 BL**) and orange (**ASP-105 O**)



TECHNICAL DATA

Built-in battery	6 V 1,2 Ah
Supply voltage	12 V DC
Enclosure dimensions	148 x 254 x 64 mm
Operating temperature range	-25...+70 °C
Standby mode current consumption	30 mA
Weight	1010 g
The intensity of sound	to 120 dB
Maximum humidity	93 ±3%
Operating frequency band	868,0 - 868,6 MHz
Radio communication range (in open area)	to 500 m
Environmental class according to EN50130-5	IV
Complied with standards	EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-4, EN 50131-5-3
Maximum current consumption - optical signaling	80 mA
Maximum current consumption - acoustic signaling	225 mA
Maximum current consumption - optical and acoustic signaling	265 mA
Security grade according to EN 50131-4	Grade 2
Name of certification body	Telefication

