

EQUIPSON GROUP

2023



Audio Installation

MARK

Wifi / Bluetooth ceiling speakers

MWCA 402 consists of two ceiling loudspeakers for installation, one amplified and the other passive. The active unit integrates a 2x40W RMS amplifier and output connections for the passive unit. They integrate a 6.5 "woofer and a 1" tweeter. They are made of white ABS plastic and incorporate a grid fixed with magnets. You can connect via Wi-Fi and Bluetooth with smartphones or devices capable of sending streaming audio files, configuring with the WiiM Home application (iOS, Android, Windows and Mac), being possible to group several units, assign channel (L or R) and control the volume. Each pair of devices includes a remote control to avoid smartphone use once the speakers are connected and playing.

Features

- Wifi and Bluetooth connectivity. Line in Stereo.
- Remote control.

Ceiling Loudspeakers

SET MWCA 402

- · WiiM Home App.
- Supplied in pairs.

Φ° TECHNICAL DATA

Туре	Ceiling speaker
Low Impedance Power	2 x 40 W
LF Transducer	Woofer 6.5"
HF Transducer	Tweeter 1"
Connectivity	Wifi / Bluetooth

Max SPL	90 dB
Frequency Range	50 Hz - 20 kHz
Dimensions	Ø242 x 127 mm



Pair of self-powered loudspeakers WIFI/Bluetooth

MWA 802 consists of a pair of installation loudspeakers, one amplified 2x40W RMS and the other passive. Both integrate a 6.5" woofer and a 1" tweeter. Made of white ABS plastic, they include a metal grill and a fixing handle. It has Wi-Fi and Bluetooth connection with smartphones or similar devices capable of sending streaming audio files. System configuration is easy using the WiiM Home application (available on iOS, Android, Windows and Mac), being possible to group several units, assign channel (L or R) and control the volume from the phone. The application has the ability to send files through Spotify, online radios, or those stored on the phone. Includes remote control.

Features

- Wifi and Bluetooth connectivity.
- · Remote control.
- App MUZO Player.
- Supplied in pairs.

TECHNICAL DATA

Туре	2 way. Active + passive
Power	2 x 40 W
LF Transducer	Woofer 6.5"
HF Transducer	Tweeter 1"
Sensitivity (1W @ 1m)	90 dB
SPL Max	105 dB
Frequency Range	50 Hz - 20 KHz

Controls	App WiiM Home
Connectivity	Wifi / Bluetooth
Enclosure material	Plastic
Grill	Metallic
Colour	White
Power supply	AC 100V / 240V 50/60 Hz External power supply 19V DC)

EQUIPSON **GROUP**













www.equipson.es

